

PRODUCT GUIDE



Aragonesa de Componentes Pasivos

Series	Size	Electrical Angle	Mechanical Angle	Technology	Electrical Law	PCB Mount	Nominal Resistance	Standard Tolerance	Max. Power Dissipation (50°C)	Max. Voltage	Mechanical Life (max.)	Oper. T ^a	Detents for feeling effect (max.)	Detents for output value discrimination (max.)
 CA6	6mm	215±20°	235±5°	Carbon	Linear	THT, SMD	100Ω-5MΩ, 100Ω-1MΩ	±20%	0.10W	100VDC	1.000	-25°C...+70°C (+85°C inquiry)	-	-
					Log or Antilog		1KΩ-2M2Ω, 1KΩ-1MΩ	±25%	0.06W	60VDC				
 CA-CE9 MCA*-MCE9*	9mm	220±20°	240±5°	Carbon	Linear	THT, SMD	100Ω-5MΩ, 100Ω-1MΩ	±20%, ±30%	0.15W	150VDC	10.000	-25°C...+70°C (+85°C inquiry)	20	10
					Log or Antilog		1KΩ-2M2Ω, 1KΩ-1MΩ		0.10W	200VDC				
				Cermet	Linear		100Ω-5MΩ	±20%	0.50W	200VDC		-40°C...+90°C (+125°C inquiry)		
					Log or Antilog		1KΩ-2M2Ω		0.20W					
 CA-CE14 MCA*-MCE14* CAR*-CER14*	14mm	245±20°	265±5°	Carbon	Linear	THT, SMD	100Ω-5MΩ, 100Ω-1MΩ	±20%, ±30%	0.25W	250VDC	10.000	-25°C...+70°C (up to +120°C, inquiry)	38	14
					Log or Antilog		1KΩ-2M2Ω, 1KΩ-1MΩ		0.13W	150VDC				
				Cermet	Linear		100Ω-5MΩ	±20%	0.70W	250VDC		-40°C...+90°C (+125°C inquiry)		
					Log or Antilog		1KΩ-2M2Ω		0.30W	200VDC				
 RS9	9mm	220±20°	245±5°	Carbon	Linear	THT, SMD	10KΩ (standard)	±30%	0.15W	200VDC	200.000	-25°C...+70°C (+85°C inquiry)	-	-
 RS14	14mm	245±20°	265±5°	Carbon	Linear	THT, SMD	10KΩ (standard)	±30%	0.15W	250VDC	250.000	-25°C...+70°C (up to +120°C, inquiry)	-	-
 CS14 MCS14*	14mm	330±20°	360±5°	Carbon	Linear	THT, SMD	1KΩ-5MΩ, 1KΩ-1MΩ	±30%	0.15W	250VDC	250.000	-25°C...+70°C (up to +120°C, inquiry)	50	16
 Q16	16mm	330±20°	360±5°	Carbon	Linear	THT	10KΩ (standard)	±30%	0.15W	250VDC	10.000	-25°C...+70°C (others inquiry)	16	16
 QJ16	16mm	245±20°	90±5°	Carbon	Linear	THT	10KΩ (standard)	±30%	0.15W	250VDC	10.000	-25°C...+70°C (others inquiry)	Spring Mechanisim	
 CSF14	36X16mm	330±20°	360±5°	Carbon	Linear	Pluggable Rast 2.5	10KΩ (standard)	±30%	0.15W	250VDC	10.000	-25°C...+70°C (others inquiry)	-	-
 QC16	36X16mm	330±20°	360±5°	Carbon	Linear	Pluggable Rast 2.5	10KΩ (standard)	±30%	0.15W	250VDC	10.000	-25°C...+70°C (others inquiry)	16	16
 QCJ16	36X16mm	330±20°	360±5°	Carbon	Linear	Pluggable Rast 2.5	10KΩ (standard)	±30%	0.15W	250VDC	10.000	-25°C...+70°C (others inquiry)	Spring Mechanisim	

* Only THT

PRODUCT GUIDE

Potentiometers

